



THE #1 CHOICE OF
PAINTING PROFESSIONALS®

SPARTAGLOSS®

Interior/Exterior Acrylic Gloss Paint W 7600V



DESCRIPTION: SPARTAGLOSS® is a quality interior/exterior acrylic gloss paint that provides very good non-blocking properties and adhesion. SPARTAGLOSS also features easy application with smooth flowing, sag resistance, and good leveling qualities. It forms a tough, washable, stain-resistant finish, making it ideal for kitchen and bathroom walls, high-traffic areas, trim and door, cabinets, interior window frames, and handrails.

PRODUCT INFORMATION

SOLVENT TYPE Waterborne		RESIN TYPE Acrylic		SURFACE PREPARATION All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded, cleaned, and spot-primed with a suitable primer or sealer. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.	
FINISH (ASTM D 523) Gloss: 70–75% on a 60° meter		SPECIAL INSTRUCTIONS			
COLORS Stock colors: Swiss Coffee. Other colors can be special ordered or store mixed.		<ul style="list-style-type: none"> CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces. For more information, see Dunn-Edwards brochure on "Surface Preparation Safety" or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or log onto www.epa.gov/lead/or/asbestos, or contact your state or local Health Department. This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting. Not recommended for use on exterior horizontal surfaces, such as handrails or balcony railings. For these types of surfaces, the Perma-Series products are recommended. Prime aged-alkyd surfaces with Ultra-Grip® (W 715) before applying SPARTAGLOSS. Do not apply when the air or surface temperature is below 50°F. 			
TINT BASES L Tintable White, MA Medium, U Ultra Deep		PRIMERS			
VISCOSITY@77°F/25°C (ASTM D 562) 95–100 KU		DRYWALL			
MAXIMUM VOC CONTENT 100 g/L (as supplied) (A)		Textured: } Untextured: } Self-priming Skim-coated: }			
SOLIDS BY VOLUME (ASTM D 2697) 36.0% ± 2%		SOLIDS BY WEIGHT 48.0 ± 2%		MASONRY	
WEIGHT PER GALLON (ASTM D 1475) 10.30 lbs.		Plaster: } Tilt-up concrete: } Super-Loc® (W 718), Eff-Stop® (W 709) Poured-in-place: } or Acri-Loc® (W 6232) Brick: } Concrete block: Blocfil (W 304 or W 305) or Concrete Block Filler (W 315) Smooth trowel: Super-Loc® (W 718) or Enduraseal® (W 360)			
COMPOSITION BY WEIGHT		WOOD/SYNTHETIC WOOD-INTERIOR			
Pigment-20.5%		Vehicle-79.5%		Trims, doors: } Masonite: } Unikote (W 707V) or Ultra-Grip® (W 715) Hardboard: } or Inter-Kote® (W 6325)	
*Prime pigments20.5		Acrylic resins25.5		WOOD-EXTERIOR	
Water & additives54.0		Trim, sash, fascia: } Rough-sawn: } E-Z Prime® (W 708) T1-11 siding: }			
*Prime pigments include titanium dioxide (TiO ₂), plus all other pigments directly adding to the hiding power of this paint.		SYNTHETIC WOOD-EXTERIOR			
RECOMMENDED FILM THICKNESS PER COAT Wet: 4.2 mils Dry: 1.5 mils		Masonite: } Hardboard: } Ultra-Grip® (W 715) MDO siding: }			
PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS Approximately 325–375 sq. ft. per gallon, depending on surface conditions.		METAL			
THINNING RECOMMENDATIONS Designed to be applied at package consistency. However, if thinning is necessary to maintain good flow and workability, add up to 1/2 pint (8 fl. oz.) of clean water per gallon.		Ferrous: Syn-Lustro® (W 8), Corrobar® (43-5), Galv-Alum™ (43-7), Bloc-Rust® (43-4) or Ultra-Grip® (W 715) – INTERIOR ONLY Non-ferrous: Syn-Lustro® (W 8), Ultra-Grip® (W 715) or Galv-Alum™ (43-7)			
AVERAGE DRY TIME@77°F/25°C (ASTM D 1640) To touch: 1–2 hours Recoat: 6–8 hours		CLEANUP Warm, soapy water			
APPLICATION EQUIPMENT Brush, roller, airless spray, HVLP spray		DISPOSAL For information on local options to dispose of unwanted, leftover paint, call 800-CLEANUP, or log onto www.cleanup.org .			
PACKAGING One-gallon, five-gallon containers		CONFORMS TO Master Painters Institute (MPI) #114 Green Seal's Standard GS-11 & LEED requirements			
STORAGE Store in a dry area. Protect from freezing. Extreme temperatures may cause paint to become unusable. For example: freezing and thawing may cause paint to gel, and high heat may cause solid skin to form.		MATERIAL SAFETY DATA SHEET Form #1			