THE #1 CHOICE OF PAINTING PROFESSIONALS®

SPARTASHELL®
Interior/Exterior Acrylic Eggshell Paint
W 7400

Contains no Ethylene Glycol or other Toxic Air Contaminants — EG-FREE®

DESCRIPTION: SPARTASHELL® is a quality interior/exterior acrylic eggshell paint that provides very good non-blocking properties and adhesion. **SPARTASHELL** also features easy application with smooth flowing, sag resistance, and good leveling qualities. It forms a tough, washable, stain-resistant finish, making it ideal for kitchen and bathroom walls, high-traffic areas, trim and door, cabinets, interior window frames, and handrails.

PRODUCT INFORMATION

SOLVENT TYPE
Waterborne

RESIN TYPE
Acrylic

FINISH (ASTM D 523)
Eggshell: 27–35% on a 60° meter

COLORS
Stock colors: Swiss Coffee. Other colors can be special ordered or store mixed.

TINT BASES
L Tintable White, MA Medium, U Ultra Deep

VISCOSITY@77°F/25°C (ASTM D 562)
95–100 KU

MAXIMUM VOC CONTENT
90 g/L (as supplied) (A)

SOLIDS BY VOLUME (ASTM D 2697)
36.0% ± 2%

SOLIDS BY WEIGHT
47.0 ± 2%

WEIGHT PER GALLON (ASTM D 1475)
10.40 lbs.

COMPOSITION BY WEIGHT

Pigment–24.0%		**Vehicle–76.0%**	
*Prime pigments	19.0	Acrylic resins	21.0
Reinforcing pigments	5.0	Water & additives	55.0

**Prime pigments include titanium dioxide (TiO_2), plus all other pigments directly adding to the hiding power of this paint.*

RECOMMENDED FILM THICKNESS PER COAT
Wet: 4.2 mils Dry: 1.5 mils

PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS
Approximately 325–375 sq. ft. per gallon, depending on surface conditions.

THINNING RECOMMENDATIONS
Designed to be applied at package consistency. However, if thinning is necessary to maintain good flow and workability, add up to 1/2 pint (8 fl. oz.) of clean water per gallon.

AVERAGE DRY TIME@77°F/25°C (ASTM D 1640)
To touch: 1–2 hours
Recoat: 4–6 hours

APPLICATION EQUIPMENT
Brush, roller, airless spray, HVLP spray

PACKAGING
One-gallon, five-gallon containers

STORAGE
Store in a dry area. Protect from freezing. Extreme temperatures may cause paint to become unusable. For example: freezing and thawing may cause paint to gel, and high heat may cause solid skin to form.

CLEANUP
Warm, soapy water

DISPOSAL
For information on local options to dispose of unwanted, leftover paint, call 800-CLEANUP, or log onto www.cleanup.org.

CONFORMS TO
Master Painters Institute (MPI) #43
Green Seal's Standard GS-11 & LEED requirements

MATERIAL SAFETY DATA SHEET
Form #1

SURFACE PREPARATION
All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded, cleaned, and spot-primed with a suitable primer or sealer. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

SPECIAL INSTRUCTIONS
- CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces. For more information, see Dunn-Edwards brochure on "Surface Preparation Safety" or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or log onto www. epa.gov/lead or/asbestos, or contact your state or local Health Department.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- Not recommended for use on exterior horizontal surfaces, such as handrails or balcony railings. For these types of surfaces, the **Perma-Series** products are recommended.
- Prime aged-alkyd surfaces with **Ultra-Grip® (W 715)** before applying **SPARTASHELL**.
- Do not apply when the air or surface temperature is below 50°F.

PRIMERS

DRYWALL
Textured:, Untextured:, Skim-coated: — **Self-priming**

MASONRY
Plaster:, Tilt-up concrete:, Poured-in-place:, Brick: — **Super-Loc® (W 718)**, **Eff-Stop® (W 709)** or **Acri-Loc® (W 6232)**
Concrete block: **Blocfil (W 304** or **W 305)** or **Concrete Block Filler (W 315)**
Smooth trowel: **Super-Loc® (W 718)** or **Enduraseal® (W 360)**

WOOD/SYNTHETIC WOOD–INTERIOR
Trims, doors:, Masonite:, Hardboard: — **Unikote (W 707V)** or **Ultra-Grip® (W 715)** or **Inter-Kote™ (W 6325)**

WOOD–EXTERIOR
Trim, sash, fascia:, Rough-sawn:, T1-11 siding: — **E-Z Prime® (W 708)**

SYNTHETIC WOOD–EXTERIOR
Masonite:, Hardboard:, MDO siding: — **Ultra-Grip® (W 715)**

METAL
Ferrous: **Ultra-Grip® (W 715)**–*INTERIOR ONLY* or **Corrobar® (43-5)**, **Galv-Alum™ (43-7)** or **Bloc-Rust® (43-4)**
Non-ferrous: **Ultra-Grip® (W 715)** or **Galv-Alum™ (43-7)**

 ©DUNN-EDWARDS CORPORATION • 4885 E. 52nd Place, Los Angeles, CA 90040 • (888) DEPAINT • dunnedwards.com

GALV-ALUM™ is a trademark of BIEC International, Inc. used under license by Dunn-Edwards Corporation.