



# Dunn's® Interior/Exterior Multi-Surface Primer DPMP00-0-WH



Dunn's Interior/Exterior Multi-Surface Primer is a Zero VOC, low odor acrylic multi-surface primer designed for a wide range of interior and exterior applications. It provides excellent adhesion to properly prepared drywall, wood, and masonry, as well as hard-to-stick surfaces, such as aged alkyd, aluminum, and galvanized metal. **Dunn's Interior/Exterior Multi-Surface Primer** has very good stain blocking, hide, and excellent enamel holdout. It applies smoothly, dries fast, and is compatible with all Dunn-Edwards latex and alkyd finishes.

## PRODUCT INFORMATION

**SOLVENT TYPE:** Waterborne | **RESIN TYPE:** Copolymer

**FINISH** (ASTM D 523): Semi-Gloss: 2–8% on a 60° meter

**COLORS:** White. Dunn's Interior/Exterior Multi-Surface Primer may be tinted with up to 2 fl. oz of colorant per gallon.

**VISCOSITY@77°F/25°C** (ASTM D 562): 98–104 KU

<b>MAXIMUM VOC CONTENT</b> 3 g/L (by ASTM Test Method D6886)	<b>MAXIMUM RAVOC</b> (Reactivity-Adjusted VOC) 1 g/L
---	---

NOTE: "Zero VOC" means "No organic solvents added." (Trace amounts of VOC may be present as residual components of other ingredients. Dunn-Edwards uses Zero VOC colorants; other additives may increase VOC emissions.)

<b>SOLIDS BY VOLUME</b> (ASTM D 2697) 36.2% ± 2%	<b>SOLIDS BY WEIGHT</b> 50.0% ± 2%
---	---------------------------------------

**WEIGHT PER GALLON** (ASTM D 1475): 10.86 lbs.

**COMPOSITION BY WEIGHT**

<b>Pigment—34.6%</b>	<b>Vehicle—65.4%</b>
----------------------	----------------------

*Prime pigments ..... 11.1	Acrylic resins ..... 12.4
Reinforcing pigments ..... 23.5	Water & additives ..... 53.0

\*Prime pigments include titanium dioxide (TiO<sub>2</sub>), plus all other pigments directly adding to the hiding power of this paint.

**RECOMMENDED FILM THICKNESS PER COAT**

Wet: 5.5 mils	Dry: 2.0 mils
---------------	---------------

**PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS**  
Approximately 225–275 sq. ft. per gallon, depending on surface conditions and application techniques.

**THINNING RECOMMENDATION:** This coating is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of coating.

**AVERAGE DRY TIME@77°F/25°C** (ASTM D 1640)  
To touch: 30–60 minutes | Recoat: After 1–2 hours  
Dry times and recoat times are temperature, humidity and film thickness dependent.

**APPLICATION EQUIPMENT:** Brush, roller, airless spray

**PACKAGING:** One-gallon, Five-gallon containers

**STORAGE:** Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable. See Paint Storage Best Practices Technical Bulletin at dunnedwards.com for more information.

**CLEANUP:** Warm, soapy water

**DISPOSAL:** For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit [www.dunnedwards.com](http://www.dunnedwards.com). **Do not mix with other products.**

**CONFORMS TO:** ARB 2007 SCM & CALGreen 2016; CHPS Section 01350; LEED 2009 IEQ Credit 4.2; LEED v4 EQ Credit 2; MPI Approved Product #17; FDA Guidelines for Resinous & Polymeric Coatings

**SAFETY DATA SHEET:** Available at [www.dunnspaints.com](http://www.dunnspaints.com)

**SURFACE PREPARATION:** All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

### SPECIAL INSTRUCTIONS

- CAUTION!** Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Wear a NIOSH-approved N95 particulate filter mask to avoid breathing dust. Use a HEPA vacuum for cleanup, and finish by water-washing all surfaces. For more information, see Dunn-Edwards brochure on "Surface Preparation Safety" or call U.S. EPA's lead hotline at 1-800-424-LEAD, or visit [www.epa.gov/lead](http://www.epa.gov/lead) or /asbestos, or contact your state or local Health Agency.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- Dunn's Interior/Exterior Multi-Surface Primer** seals and blocks out most household stains, such as crayon, pencil, ink, and felt marker. After priming stained areas, test that the stain has been sealed by applying the topcoat to a small area. More than one coat may be necessary on severe stains. **Dunn's Interior/Exterior Multi-Surface Primer** may block minor dried water stains, however, a solvent-based stain blocking primer, such as pigmented shellac, is recommended.
- Galvanized metal must be cleaned with a solvent or a water-soluble degreasing cleaner to remove all oils prior to etching. Change wiping material and cleaning solution frequently so the oils are removed from the surface, not just spread around. Surface should then be etched with **Supreme Chemical Metal Clean & Etch (ME01)**.
- Dunn's Interior/Exterior Multi-Surface Primer** can be used on bare ferrous metal surfaces (interior only) provided that they are free of rust, mill scale, and other contaminants. Before any surface preparation is attempted, oil and grease must be removed by employing SSPC-SP11 Power Tool Cleaning to Bare Metal to remove mill scale, rust, or other contaminants and to leave a roughened surface.
- Before applying over previously painted surfaces, **Dunn's Interior/Exterior Multi-Surface Primer** should be tested for adhesion and compatibility.
- On Level 4 and 5 Drywall Finishes, thin **Dunn's Interior/Exterior Multi-Surface Primer** with 10% of clean water (3/4 pint per gallon / 1/2 gallon per 5-gallon) for best penetration.
- Allow to dry overnight before applying solvent-based epoxy and urethane topcoats - **INTERIOR ONLY**.
- Do not apply when the air or surface temperature is below 50°F.

### USE AS A PRIMER FOR

**WALLBOARD & MASONRY:** Dunn's Interior/Exterior Multi-Surface Primer can be applied on surfaces with a pH of up to 13.

Drywall: Stucco: Concrete: Brick:	} <b>Dunn's Interior/Exterior Multi-Surface Primer</b>
--	--

**WOOD-INTERIOR**  
Trim, doors: **Dunn's Interior/Exterior Multi-Surface Primer**

<b>WOOD-EXTERIOR</b> Trim, sash: T1-11 siding:	} <b>Dunn's Interior/Exterior Multi-Surface Primer</b>
--	--

<b>SYNTHETIC WOOD</b> Masonite: Hardboard:	} <b>Dunn's Interior/Exterior Multi-Surface Primer</b>
--	--

<b>METAL</b> Ferrous:  Non-ferrous:	} <b>Dunn's Interior/Exterior Multi-Surface Primer</b>
--	--



**Dunn's®**  
**Interior/Exterior**  
**Multi-Surface Primer**  
**DPMP00-0-WH**



**PRODUCT INFORMATION**

**HEALTH & SAFETY CAUTIONS:** INHALATION OF SPRAY MIST OR SANDING DUST MAY BE HARMFUL. Use only with adequate ventilation. Avoid breathing vapors, spray mist and sanding dust. Wear NIOSH-approved N95 particulate filter mask when spraying or sanding. Avoid contact with skin and eyes. Do not ingest. Close container after each use. **FIRST AID:** If swallowed, immediately give 1 or 2 glasses of water to drink – for emergency information, call 1-800-222-1222. If having difficulty breathing, move to fresh air. For eye contact, immediately flush with water for 15 minutes. For skin contact, wash thoroughly with soap and water.

• **KEEP OUT OF REACH OF CHILDREN** •

Ingredient (CAS #): Water (7732-18-5); Copolymer Resin (Proprietary); Talc, NonAsbestos (14087-96-6); Kaolin Clay (1332-58-7); Titanium Dioxide (13463-67-7).

⚠ **WARNING:** Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)