



# Dunn's® PAINTS SELECT

## Interior/Exterior Semi-Gloss Paint

### DSIE55



Dunn's PAINTS SELECT Interior/Exterior Semi-Gloss Paint is a professional interior/exterior, ultra-low VOC, 100% acrylic semi-gloss paint. Dunn's PAINTS SELECT Interior/Exterior Semi-Gloss Paint provides good hide, block resistance, adhesion, and dirt pick-up resistance, and can be used on properly prepared and primed masonry, stucco, wood, trim and doors, and metal. Can be used down to surface and air temperature of 35° F (1.67° C).

## PRODUCT INFORMATION

<b>SOLVENT TYPE:</b> Waterborne		<b>RESIN TYPE:</b> 100% Acrylic
<b>FINISH</b> (ASTM D 523): Semi-Gloss: 40–50% on a 60° meter		
<b>COLORS:</b> All colors can be special ordered or store mixed.		
<b>TINT BASES:</b> L Tintable White, M Medium, U Ultra Deep		
<b>VISCOSITY@77°F/25°C</b> (ASTM D 562): 91–101 KU		
<b>MAXIMUM VOC CONTENT</b> 50 g/L (as supplied)	<b>MAXIMUM RAVOC</b> (Reactivity-Adjusted VOC) 15 g/L	
<b>SOLIDS BY VOLUME</b> (ASTM D 2697) 33.8% ± 2%	<b>SOLIDS BY WEIGHT</b> 43.4% ± 2%	
<b>WEIGHT PER GALLON</b> (ASTM D 1475): 9.90 lbs.		

COMPOSITION BY WEIGHT	
<b>Pigment—18.3%</b>	<b>Vehicle—81.7%</b>
*Prime pigments .....16.8	Resin solids..... 22.5
Reinforcing pigments .....1.5	Water & additives .....59.2

*\*Prime pigments include all pigments directly adding to the hiding power of this paint.*

RECOMMENDED FILM THICKNESS PER COAT	
Wet: 4.4 mils	Dry: 1.5 mils

**PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS**  
Approximately 325–375 sq. ft. per gallon, depending on surface conditions and application techniques.

**THINNING RECOMMENDATION:** This coating is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of coating.

<b>AVERAGE DRY TIME@77°F/25°C</b> (ASTM D 1640)	
To touch: 1–2 hours	Recoat: 4–6 hours
Dry times and recoat times are temperature, humidity and film thickness dependent.	

**APPLICATION EQUIPMENT:** Brush, roller, airless spray

AIRLESS SPRAY	BRUSH	ROLLER
<b>PRESSURE:</b> 1800-2500psi <b>TIP:</b> .015"-.017"	Nylon/Polyester	3/8"-1" Pro White or microfiber roller cover

**PACKAGING:** Quart, one-gallon, five-gallon containers

**STORAGE:** Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable. See *Paint Storage Best Practices* Technical Bulletin at [dunnedwards.com](http://dunnedwards.com) for more information.

**CLEANUP:** Warm, soapy water

**DISPOSAL:** For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit [www.dunnedwards.com](http://www.dunnedwards.com). **Do not mix with other products.**

**CONFORMS TO:** ARB 2007 SCM & CALGreen 2022; MPI Approved Product #11, #54

**SAFETY DATA SHEET:** Available at [www.dunnspaints.com](http://www.dunnspaints.com)

**SURFACE PREPARATION:** All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

### SPECIAL INSTRUCTIONS

- CAUTION!** Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Wear a NIOSH-approved N100 particulate filter mask to avoid breathing dust. Use a HEPA vacuum for cleanup, and finish by water-washing all surfaces. For more information, see Dunn-Edwards brochure on "Surface Preparation Safety" or call U.S. EPA's lead hotline at 1-800-424-LEAD, or visit [www.epa.gov/lead](http://www.epa.gov/lead) or asbestos, or contact your state or local Health Agency.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- If efflorescence exists, remove all noticeable deposits and prime the entire surface with **Dunn's PAINTS Multi-Surface Primer**.
- Certain woods, such as redwood, cedar, and spruce, contain water-soluble extracts (tannins) that may discolor lighter colors. In these situations, it is recommended to prime the wood with **Dunn's PAINTS Multi-Surface Primer** before applying **Dunn's PAINTS SELECT Interior/Exterior Semi-Gloss**.
- For best results, use airless spray application.
- When the air temperature is at 35°F, substrates may be colder; prior to painting, check to be sure the air, surface, and material temperature are above 35°F and at least 5°F above the dew point. Avoid using if rain or snow is expected within 2-3 hours, as in colder temperatures, it may require longer time before the paint film cures enough not to be affected by rain or snow. Do not apply at air or surface temperatures below 35°F or when air or surface temperatures may drop below 35°F within 48 hours.
- Standard latex primers cannot be used below 50°F. See the specific primer product information sheet for that product's application conditions.

### PRIMERS

#### DRYWALL

Textured:  
 Untextured: **Dunn's PAINTS Multi-Surface Primer**  
 Skim-coated:

#### MASONRY

Plaster:  
 Tilt-up concrete:  
 Poured-in-place:  
 Brick: } **Dunn's PAINTS Multi-Surface Primer**

Concrete block: **Dunn's PAINTS Multi-Surface Primer**

#### WOOD

Trim, sash, fascia: } **Dunn's PAINTS Multi-Surface Primer**  
 T1-11 siding:  
 Rough-sawn: **Self-priming** (see **SPECIAL INSTRUCTIONS**)

#### SYNTHETIC WOOD

Masonite:  
 Hardboard:  
 MDO siding: } **Dunn's PAINTS Multi-Surface Primer**

#### METAL

Ferrous: **Dunn's PAINTS Multi-Surface Primer**

Non-ferrous: **Dunn's PAINTS Multi-Surface Primer**

Galvanized steel: **Dunn's PAINTS Multi-Surface Primer**

*\*for incidental use on galvanized*



# Dunn's® PAINTS SELECT

Interior/Exterior  
Semi-Gloss Paint  
DSIE55



## PRODUCT INFORMATION

**HEALTH & SAFETY CAUTIONS:** INHALATION OF SPRAY MIST OR SANDING DUST MAY BE HARMFUL. Use only with adequate ventilation. Avoid breathing vapors, spray mist and sanding dust. Wear NIOSH-approved N100 particulate filter mask when spraying or sanding. Avoid contact with skin and eyes. Do not ingest. Close container after each use. **FIRST AID:** If swallowed, immediately give 1 or 2 glasses of water to drink – for emergency information, call 1-800-222-1222. If having difficulty breathing, move to fresh air. For eye contact, immediately flush with water for 15 minutes. For skin contact, wash thoroughly with soap and water.

• KEEP OUT OF REACH OF CHILDREN •

Ingredients (CAS #): Water (7732-18-5); Copolymer Resin (Proprietary); Titanium Dioxide (13463-67-7); Nepheline Syenite (37244-96-5); Ester Alcohol (25265-77-4).

⚠ **WARNING:** Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)